

MODEL NAME	DC-015-x-S124
SCHEMATIC	
CENTER PIN	$\phi 1.0$ $\phi 1.3$

### SPECIFICATION


- Rating : DC 30V 1.0A ;
- Contact resistance :  $\leq 50m\Omega$  ;
- Insulation resistance :  $\geq 100M\Omega$  ;
- Withstand voltage : 500VAC ;
- Insertion and extraction force : 3-20N;
- life test : 5,000 cycles °

NO.	DESCRIPTION	QTY	MATERIAL	PLATING
④	PIN	1	BRASS	Ag-Plating
③	CURVE PIECE	1	BRASS	Ag-Plating
②	SPRING	1	STAINLESS STEEL	Ag-Plating
①	HOUSING	1	PA9T	

**KSD** 科斯达电子科技有限公司  
 SWITCH CONNECTOR KSD ELECTRONIC TECHNOLOGY Co., LTD  
 全球 互联零组件制造企业

TOLERANCE UNLESS OTHERWISE STATED :  
 Up to 5 ±0.2  
 Above 5 ~ 15 ±0.3  
 Above 15 ~ 30 ±0.4  
 Above 30 ~ 50 ±0.5  
 Angle ±0.3°

3RD. ANGEL'S



UNITS

MM

DRAWN BY: Jack Lu  
 DATE: 04/07/17  
 CHECKED BY: Jacky Chen  
 DATE: 04/07/17  
 APPROVED BY: Tony Kao  
 DATE: 04/07/17

MAT'L		TITLE	JACK
FINISH		MODLE	DC JACK
SCALE	1 : 1	DWG NO.	DC-015-x-S124
SHEET NO.	1 of 1	PART NO.	DC-015-x-S124

ITEM NO.	DESCRIPTION	DRAWN	DATE
1	更新為A0版	Jack	040717

SIZE  
A4  
VER  
A0