



MODEL NO.	DC-060D-x-S187
SCHEMATIC	2
	1
	3
CENTER PIN	$\phi 1.0$ mm
	$\phi 1.3$ mm

SPECIFICATION

- Rating : DC 16V 2.0A
- Contact resistance : $\leq 50m\Omega$
- Insulation resistance : $\geq 100M\Omega$
- Withstand voltage : 500VAC
- Insertion and extraction force : 3-30N
- life test : 5,000 cycles

NO.	DESCRIPTION	QTY	MATERIAL	PLATING
④	HOUSING	1	PA9T(Black)	
③	TERMINAL#3	1	PHOSPHOR BRONZE	Ag-Plating
②	TERMINAL#2	1	PHOSPHOR BRONZE	Ag-Plating
①	TERMINAL#1	1	BRASS	Ag-Plating

KSD 科斯达电子科技有限公司
 SWITCH CONNECTOR KSD ELECTRONIC TECHNOLOGY Co., LTD
 全球 互 联 零 组 件 制 造 企 业

TOLERANCE UNLESS OTHERWISE STATED:
 Up to 5 ±0.2
 Above 5 ~ 15 ±0.3
 Above 15 ~ 30 ±0.4
 Above 30 ~ 50 ±0.5
 Angle ±0.3°

3RD. ANGEL'S

UNITS MM

DRAWN BY:	DATE	MAT'L	TITLE	JACK
Jack Lu	11/02/15			
CHECKED BY:	DATE	FINISH	MODLE	DC JACK
Jacky Chen	11/02/15			
APPROVED BY:	DATE	SCALE	DWG NO.	DC-060D-x-S187
Tony Kao	11/02/15	1:1		
		SHEET NO.	PART NO.	DC-060D-x-S187
		1 of 1		

ITEM NO.	DESCRIPTION	DRAWN	DATE
1	新增SPEC	Jack	110215

SIZE	A4
VER	R1