

Model No.	DC-D096-x
SCHEMATIC	
CENTER PIN	Ø2.00 mm
	Ø2.50 mm

### SPECIFICATIONS


1. Rating : DC 30V 1.0A
2. Contact resistance :  $\leq 0.03 \Omega$
3. Insulation resistance :  $\geq 100M\Omega$  (DC250V)
4. Withstand voltage : 500VAC
5. Insertion and extraction force : 3-20N
6. life test : 5,000 cycles

6	PIN	1	BRASS	Ni-Plating
5	FLAT FOOT	1	BRASS	Ag-Plating
4	CURVE PIECE	1	BRASS	Ag-Plating
3	SPRING PIECE	1	SUS301	Ag-Plating
2	COVER	1	PA9T	
1	HOUSING	1	PA9T	
NO.	DESCRIPTION	QTY	MATERIAL	PLATING

**KSD** 科斯达电子科技有限公司  
 SWITCH CONNECTOR KSD ELECTRONIC TECHNOLOGY Co., LTD  
 全球 互联零组件制造企业

TOLERANCE UNLESS OTHERWISE STATED:  
 Up to 5 ±0.2  
 Above 5 ~ 15 ±0.3  
 Above 15 ~ 30 ±0.4  
 Above 30 ~ 50 ±0.5  
 Angle ±0.3°

3RD. ANGEL'S



UNITS MM

DRAWN BY: Jack Lu DATE: 04/10/14  
 CHECKED BY: Jacky Chen DATE: 04/10/14  
 APPROVED BY: Tony Kao DATE: 04/10/14

MAT'L		TITLE	JACK
FINISH		MODLE	DC JACK
SCALE	1 : 1	DWG NO.	DC-D096-x-S125
SHEET NO.	1 of 1	PART NO.	DC-D096-x-S125

1	新增LOGO	Jack	041014
ITEM NO.	DESCRIPTION	DRAWN	DATE

SIZE A4  
 VER R1