

SCHEMATIC

SPECIFICATIONS:

CONTACT RATING : 3 AMPS @ 120 V AC or 28 V DC.
 1 AMPS @ 250 V AC or 0.4VA AMPS @ 20V AC OR DC
 ELECTRICAL LIFE : 6,000 make-and-break cycles at full load.
 CONTACT RESISTANCE : 10 mΩ max. initial @ 2-4 VDC
 100 mA , for both silver and gold plated contacts.
 INSULATION RESISTANCE : 1,000 MΩ min
 DIELETRIC STRENGTH : 1,000 V RMS @ sea level.
 OPERATING TEMPERTURE : -30°C to 130°C

MATERIALS:


CASE : Dially phthalate (DAP)(UL-94V-0)
 ACTUATOR : Nylon.
 HOUSING : Stainless steel.
 TERMINAL/CONTACT : Brass , with silver or gold plated.
 or gold over silver
 SWITCH SUPPORT : Brass , tin plated.

Model No.	TYPE		
	DS-10	ON	NONE
DS-11	ON	OFF	ON
Tem. Comm.	2-1	OPEN	2-3

KSD 科斯达电子科技有限公司
 SWITCH CONNECTOR KSD ELECTRONIC TECHNOLOGY Co., LTD
 全球 互联零组件制造企业

TOLERANCE UNLESS OTHERWISE STATED :
 Up to 5 ±0.2
 Above 5 ~ 15 ±0.3
 Above 15 ~ 30 ±0.4
 Above 30 ~ 50 ±0.5
 Angle ±0.3°

3RD. ANGEL'S



UNITS MM

DRAWN BY:	DATE	MAT'L	TITLE	SWITCH
Jack Lu	04/13/16			
CHECKED BY:	DATE	FINISH	MODLE	SLIDE SWITCH 端子截齊
Jacky Chen	04/13/16			
APPROVED BY:	DATE	SCALE	DWG NO.	DS-1xA4
Tony Kao	04/13/16	1 : 1		
		SHEET NO.	PART NO.	DS-1xA4
		1 of 1		

SIZE A4
 VER R2