



(Number of Conductors) N	X
(Pitch) P	0.50mm
(Total Pitch) Pt	X
(Total Length) L	X
(Film Length) IL	X
(Margin Width) M	X
(Total Width) W	X
(Strip Length) S1	X
(Strip Length) S2	X
(Stiffener) B1	X
(Stiffener) B2	X
(Slanting) A1	X
(Slanting) A2	X
(Terminal thickness) t	X
(Thickness) T	X

ITEM	DESCRIPTION	SPECIFICATION	REMARK
4	補強板 (Connecting)	0.225 (深藍色)	
3	上絕緣膠 (Top Insulation)	0.06(白/印字white/printed)	
2	下絕緣膠 (Under Insulation)	0.06(白white)	
1	導體 (Conductor)	0.035×0.3 (鍍錫Tin Plating)	

科斯达电子科技有限公司 SWITCH CONNECTOR KSD ELECTRONIC TECHNOLOGY Co., LTD 全球 互聯零組件製造企業				DRAWN BY: Jack Lu CHECKED BY: Jacky Chen APPROVED BY: Tony Kao		DATE: 11/27/15 DATE: 11/27/15 DATE: 11/27/15		MAT'L FINISH SCALE: 1:1 SHEET NO. 1 of 1		TITLE: FFC CABLE MODLE: FFC CABLE DWG NO.: FC11-xxx-S281 PART NO.: FC11-xxx-S281	
TOLERANCE UNLESS OTHERWISE STATED: Up to 5 ±0.2 Above 5 ~ 15 ±0.3 Above 15 ~ 30 ±0.4 Above 30 ~ 50 ±0.5 Angle ±0.3°				3RD. ANGEL'S		UNITS: MM		SIZE: A4 VER: R			