



(Number of Conductors) N	X
(Pitch) P	1.00mm
(Total Pitch) Pt	X
(Total Length) L	X
(Film Length) IL	X
(Margin Width) M	X
(Total Width) W	X
(Strip Length) S1	X
(Strip Length) S2	X
(Stiffener) B1	X
(Stiffener) B2	X
(Slanting) A1	X
(Slanting) A2	X
(Terminal thickness) t	X
(Thickness) T	X

規格 (Spec)	1.0×X×X×C1 (X/X/X/X) (0.035×0.65) (0.06+0.06)UL20624		
4	補強板 (Connecting)	0.225 (深藍色)	
3	上絕緣膠 (Top Insulation)	0.06 (白/印字white/printed)無鹵素皮膜	
2	下絕緣膠 (Under Insulation)	0.06 (白white)無鹵素皮膜	
1	導體 (Conductor)	0.035×0.65 (Tin Plating)	
ITEM	DESCRIPTION	SPECIFICATION	REMARK

KSD 科斯达电子科技有限公司
 SWITCH CONNECTOR KSD ELECTRONIC TECHNOLOGY Co., LTD
 全球 互聯零組件 制造企业

TOLERANCE UNLESS OTHERWISE STATED:
 Up to 5 ±0.2
 Above 5 ~ 15 ±0.3
 Above 15 ~ 30 ±0.4
 Above 30 ~ 50 ±0.5
 Angle ±0.3

3RD. ANGEL'S

UNITS MM

DRAWN BY: Jack Lu DATE: 11/27/15
 CHECKED BY: Jacky Chen DATE: 11/27/15
 APPROVED BY: Tony Kao DATE: 11/27/15

MAT'L TITLE: FFC CABLE
 FINISH MODLE: FFC CABLE
 SCALE: 1:1 DWG NO.: FC13-xxxxx-S281
 SHEET NO.: 1 of 1 PART NO.: FC13-xxxxx-S281

SIZE: A4
 VER: R

ITEM NO.	DESCRIPTION	DRAWN	DATE