



(Number of Conductors) N	X
(Pitch) P	0.50mm
(Total Pitch) Pt	X
(Total Length) L	X
(Film Length) IL	X
(Margin Width) M	X
(Total Width) W	X
(Strip Length) S1	X
(Strip Length) S2	X
(Stiffener) B1	X
(Stiffener) B2	X
(Slanting) A1	X
(Slanting) A2	X
(Terminal thickness) t	X
(Thickness) T	X

ITEM	DESCRIPTION	SPECIFICATION	REMARK
4	補強板 (Connecting)	0.225 (深藍色)	
3	上絕緣膠 (Top Insulation)	0.06無鹵素皮膜 (白/印字white/printed)	白色絕緣膠 綠色印字
2	下絕緣膠 (Under Insulation)	0.06無鹵素皮膜 (白white)	
1	導體 (Conductor)	0.035×0.3 (鍍錫Tin plating)	

KSD 科斯达电子科技有限公司
SWITCH CONNECTOR KSD ELECTRONIC TECHNOLOGY Co., LTD
全球 互聯零組件 制造企业

TOLERANCE UNLESS OTHERWISE STATED:
Up to 5 ±0.2
Above 5 ~ 15 ±0.3
Above 15 ~ 30 ±0.4
Above 30 ~ 50 ±0.5
Angle ±0.3°

3RD. ANGEL'S

UNITS MM

DRAWN BY: Jack Lu DATE: 11/27/15
CHECKED BY: Jacky Chen DATE: 11/27/15
APPROVED BY: Tony Kao DATE: 11/27/15

MAT'L TITLE: FFC CABLE
FINISH MODLE: FFC CABLE
SCALE: 1:1 DWG NO.: FD11-xxx-S281
SHEET NO.: 1 of 1 PART NO.: FD11-xxx-S281

SIZE: A4
VER: R

ITEM NO.	DESCRIPTION	DRAWN	DATE