



NOTE

1. Material
cj: Brass 3602
2. Plating
cj: Au over NI
3. Electrical
Rated current & voltage: DC 12V; 1.0A Max
4. To ensure the best usage, please operate it based on the working height
Based on the engineering drawings, shall not exceed the maximum allowed compression
5. To avoid arcing issue, The adaptor start to power supply after connector mated fully.

KSD 科斯达电子科技有限公司
 SWITCH CONNECTOR KSD ELECTRONIC TECHNOLOGY Co., LTD
 全球 互联零组件制造企业

TOLERANCE UNLESS OTHERWISE STATED:	Up to 5 ±0.2	Above 5 ~ 15 ±0.3	Above 15 ~ 30 ±0.4	Above 30 ~ 50 ±0.5	Angle ±0.3°	3RD. ANGEL'S	UNITS	MM
------------------------------------	--------------	-------------------	--------------------	--------------------	-------------	--------------	-------	----

DRAWN BY:	DATE	MAT'L	TITLE	CONNECTOR
Jack Lu	10/19/17			
CHECKED BY:	DATE	FINISH	MODLE	POGO PIN
Jacky Chen	10/19/17			
APPROVED BY:	DATE	SCALE	DWG NO.	PGC-20765-6P-S353
Tony Kao	10/19/17	1 : 1	PART NO.	PGC-20765-6P-S353
		SHEET NO.	1 of 1	

ITEM NO.	DESCRIPTION	DRAWN	DATE