



RECOMMENDED SOLDER PAD LAYOUT

SPECIFICATION

- 1.Rating : DC 12V 1.0A
- 2.Contact resistance : ≤50mΩ
- 3.Insulation resistance : ≥100MΩ
- 4.Withstand voltage : 500VAC
- 5.Insertion and extraction force : 3-30N
- 6.life test : 5,000 cycles

*MATERIAL

- TERMINAL 1 : PHOSPHOR BRONZE
- TERMINAL 2 : PHOSPHOR BRONZE
- TERMINAL 3 : PHOSPHOR BRONZE
- TERMINAL 4 : PHOSPHOR BRONZE
- TERMINAL 10 : BRASS
- HOUSING : PA6T

MODEL NO.	PJ-2775D	PJ-2774D	PJ-2774AD
SCHEMATIC			

KSD 科斯达电子科技有限公司
 SWITCH CONNECTOR KSD ELECTRONIC TECHNOLOGY Co., LTD
 全球 互联零组件制造企业

TOLERANCE UNLESS OTHERWISE STATED :	Up to 5 ±0.2	Above 5 ~ 15 ±0.3	Above 15 ~ 30 ±0.4	Above 30 ~ 50 ±0.5	Angle ±0.3°
	3RD. ANGEL'S	UNITS	MM		

DRAWN BY:	DATE	MAT'L	TITLE	JACK
Jack Lu	11/04/15		MODLE	PHONE JACK
CHECKED BY:	DATE	FINISH	DWG NO.	PJ-277xD
Jacky Chen	11/04/15		PART NO.	PJ-277xD
APPROVED BY:	DATE	SCALE	1:1	
Tony Kao	11/04/15	SHEET NO.	1 of 1	

1	新增SPEC	Jack	110415
ITEM NO.	DESCRIPTION	DRAWN	DATE

SIZE	A4
VER	R1