

RECOMMENDED
SOLDER PAD LAYOUT

SPECIFICATION

1. Rating : DC 12V 1.0A
2. Contact resistance : $\leq 50m\Omega$
3. Insulation resistance : $\geq 100M\Omega$
4. Withstand voltage : 500VAC
5. Insertion and extraction force : 3-30N
6. life test : 5,000 cycles

*MATERIAL


- TERMINAL 1 : PHOSPHOR BRONZE
- TERMINAL 2 : PHOSPHOR BRONZE
- TERMINAL 3 : PHOSPHOR BRONZE
- TERMINAL 10 : BRASS
- TERMINAL 11 : PHOSPHOR BRONZE
- HOUSING : PA6T

MODEL NO.	PJ-2875D	PJ-2874AD	PJ-2874BD	PJ-2873D	PJ-2873AD
SCHEMATIC					

KSD 科斯达电子科技有限公司
SWITCH CONNECTOR 全球互联网组件制造企业
KSD ELECTRONIC TECHNOLOGY Co., LTD

TOLERANCE UNLESS OTHERWISE STATED:
Up to 5 ±0.2
Above 5 ~ 15 ±0.3
Above 15 ~ 30 ±0.4
Above 30 ~ 50 ±0.5
Angle ±0.3°

3RD. ANGEL'S



UNITS

MM

DRAWN BY: Jack Lu DATE: 11/04/15
CHECKED BY: Jacky Chen DATE: 11/04/15
APPROVED BY: Tony Kao DATE: 11/04/15

MAT'L	TITLE	JACK
FINISH	MODLE	PHONE JACK
SCALE 1:1	DWG NO.	PJ-287xD
SHEET NO. 1 of 1	PART NO.	PJ-287xD

ITEM NO.	DESCRIPTION	DRAWN	DATE
1	新增SPEC	Jack	110415

SIZE A4
VER R1