


RECOMMENDED SOLDER PAD LAYOUT

SPECIFICATION

1. Rating : DC 12V 1.0A
2. Contact resistance :  $\leq 50m\Omega$
3. Insulation resistance :  $\geq 100M\Omega$
4. Withstand voltage : 500VAC
5. Insertion and extraction force : 3-30N
6. life test : 5,000 cycles

\*MATERIAL

- TERMINAL 1 : PHOSPHOR BRONZE
- TERMINAL 2 : BRASS
- TERMINAL 3 : BRASS
- TERMINAL 4 : PHOSPHOR BRONZE
- TERMINAL 10 : PHOSPHOR BRONZE
- TERMINAL 11 : PHOSPHOR BRONZE
- HOUSING : PA6T




MODEL NO.	PJ-297D	PJ-2975AD	PJ-2975BD	PJ-2974D
SCHEMATIC				

**KSD** 科斯达电子科技有限公司  
 SWITCH CONNECTOR KSD ELECTRONIC TECHNOLOGY Co., LTD  
 全球 互联网 零组件 制造企业

TOLERANCE UNLESS OTHERWISE STATED:  
 Up to 5 ±0.2  
 Above 5 ~ 15 ±0.3  
 Above 15 ~ 30 ±0.4  
 Above 30 ~ 50 ±0.5  
 Angle ±0.3°

3RD. ANGEL'S



UNITS

MM

DRAWN BY:	DATE
Jack Lu	11/04/15
CHECKED BY:	DATE
Jacky Chen	11/04/15
APPROVED BY:	DATE
Tony Kao	11/04/15

MAT'L	TITLE	JACK
FINISH	MODLE	PHONE JACK
SCALE	DWG NO.	PJ-297xD
SHEET NO.	PART NO.	PJ-297xD
1 of 1		

1	新增SPEC	Jack	110415
ITEM NO.	DESCRIPTION	DRAWN	DATE

SIZE  
A4  
VER  
R1