

**\*MATERIAL**

- TERMINAL 1 : PHOSPHOR BRONZE
- TERMINAL 2 : PHOSPHOR BRONZE
- TERMINAL 3 : PHOSPHOR BRONZE
- TERMINAL 4 : PHOSPHOR BRONZE
- TERMINAL 5 : PHOSPHOR BRONZE
- TERMINAL 10 : BRASS
- TERMINAL 11 : BRASS
- HOUSING : PA6T

**SPECIFICATION**


1. Rating : DC 12V 1.0A
2. Contact resistance :  $\leq 50m\Omega$
3. Insulation resistance :  $\geq 100M\Omega$
4. Withstand voltage : 500VAC
5. Insertion and extraction force : 3-30N
6. life test : 5,000 cycles

MODEL NO.	PJ-3827D	PJ-3825D
SCHMATIC		

**KSD** 科斯达电子科技有限公司  
 SWITCH CONNECTOR 全球 互联零组件制造企业  
 KSD ELECTRONIC TECHNOLOGY Co., LTD

TOLERANCE UNLESS OTHERWISE STATED:  
 Up to 5 ±0.2  
 Above 5 ~ 15 ±0.3  
 Above 15 ~ 30 ±0.4  
 Above 30 ~ 50 ±0.5  
 Angle ±0.3°

3RD. ANGEL'S



UNITS MM

DRAWN BY:	DATE
Jack Lu	11/03/15
CHECKED BY:	DATE
Jacky Chen	11/03/15
APPROVED BY:	DATE
Tony Kao	11/03/15

MAT'L	TITLE	JACK
FINISH	MODLE	PHONE JACK
SCALE	DWG NO.	PJ-382xD
SHEET NO.	PART NO.	PJ-382xD
1 of 1		

SIZE	A4
VER	R2

ITEM NO.	DESCRIPTION	DRAWN	DATE
2	新增SPEC	Jack	110315
1	更新圖面	Jack	041614