



P.C.B LAYOUT MOUNTING PATTERN

SPECIFICATION

1. Rating : DC 30V 0.5A ;
2. Contact resistance : $\leq 30m\Omega$;
3. Insulation resistance : $\geq 100M\Omega$ (DC250V) ;
4. Withstand voltage : 500VAC ;
5. Insertion and extraction force : 3-30N
6. life test : 5,000 cycles °

MODEL NO.	PJ-D2016-S187
SCHEMATIC	

NO.	DESCRIPTION	QTY	MATERIAL	PLATING
4	HOUSING	1	PA66(Black)	
3	CONTACT FOOT	1	Phosphor Bronze	Ag-Plating
2	CONTACT FOOT	1	Phosphor Bronze	Ag-Plating
1	CONTACT FOOT	1	Phosphor Bronze	Ag-Plating

KSD 科斯达电子科技有限公司
 SWITCH CONNECTOR KSD ELECTRONIC TECHNOLOGY Co., LTD
 全球 互联零组件制造企业

TOLERANCE UNLESS OTHERWISE STATED :
 Up to 5 ±0.2
 Above 5 ~ 15 ±0.3
 Above 15 ~ 30 ±0.4
 Above 30 ~ 50 ±0.5
 Angle ±0.3°

3RD. ANGEL'S

UNITS MM

DRAWN BY:	DATE	MAT'L	TITLE	JACK
Jack Lu	03/15/13			
CHECKED BY:	DATE	FINISH	MODLE	PHONE JACK
Jacky Chen	03/15/13			
APPROVED BY:	DATE	SCALE	DWG NO.	PJ-D2016-S187
Tony Kao	03/15/13	1:1		
		SHEET NO.	PART NO.	PJ-D2016-S187
		1 of 1		

ITEM NO.	DESCRIPTION	DRAWN	DATE
1	更新尺寸	Jack	031513

SIZE	A4
VER	R1