



SPECIFICATION

- Contact resistance : $\leq 30m\Omega$
- Insulation resistance : $\geq 100M\Omega$
- Withstand voltage : 500VAC
- Insertion and extraction force : 6-20N
- life test : 5,000 cycles
- Waterproof Lever: IPx7

ITEM	PART NAME	TERMINAL	QTY	MATERIAL	REMARK
⑩	OVAL RING	----	1	SILICONE	
⑨	BOND	----	1	EPOXY	----
⑧	TERMINAL	----	2	C2680	
⑦	TIP SPRING-2	⑤	1	Ti-Cu	Gold PLATED ,Nickel Underplate
⑥	RING SPRING-2	④	1	Ti-Cu	
⑤	RING SPRING-1	③	1	Ti-Cu	
④	TIP SPRING-1	②	1	Ti-Cu	
③	EARTH SPRING	①	1	Ti-Cu	
②	COVER	----	1	PA9T	
①	HOUSING	----	1	PA9T	

KSD 科斯达电子科技有限公司
 SWITCH CONNECTOR KSD ELECTRONIC TECHNOLOGY Co., LTD
 全球 互 联 零 组 件 制 造 企 业

TOLERANCE UNLESS OTHERWISE STATED :	Up to 5 ±0.2	3RD. ANGEL'S	UNITS	MM
	Above 5 ~ 15 ±0.3			
	Above 15 ~ 30 ±0.4			
	Above 30 ~ 50 ±0.5			
	Angle ±0.3°			

DRAWN BY:	DATE	MAT'L	TITLE	JACK
Jack Lu	04/12/19			
CHECKED BY:	DATE	FINISH	MODLE	3.5mm PHONE JACK 防水型
Jacky Chen	04/12/19			
APPROVED BY:	DATE	SCALE	DWG NO.	PJ-WP35383E-S404
Tony Kao	04/12/19	1:1		
		SHEET NO.	PART NO.	PJ-WP35383E-S404
		1 of 1		

ITEM NO.	DESCRIPTION	DRAWN	DATE