



SPECIFICATION

- 1.Contact resistance : $\leq 30m \Omega$
- 2.Insulation resistance : $\geq 100M \Omega$
- 3.Withstand voltage : 500VAC
- 5.Insertion and extraction force : 4-20N
- 6.life test : 5,000 cycles
- 7.Waterproof Lever: IPx7

ITEM	PART NAME	TERMINAL	QTY	MATERIAL	REMARK
⑩	OVAL RING	----	1	SILICONE	
⑨	BOND	----	1		----
⑧	TERMINAL	----	2	C2680	Ti PLATED OVER Ni
⑦	TIP SPRING-2	⑤	1	Ti-Cu	Ni PLATED OVER Au
⑥	RING SPRING-2	④	1	Ti-Cu	Ni PLATED OVER Au
⑤	RING SPRING-1	③	1	Ti-Cu	Ni PLATED OVER Au
④	TIP SPRING-1	②	1	Ti-Cu	Ni PLATED OVER Au
③	EARTH SPRING	①	1	Ti-Cu	Ni PLATED OVER Au
②	COVER	----	1	PA9T	
①	HOUSING	----	1	PA9T	

KSD 科斯达电子科技有限公司
 SWITCH CONNECTOR KSD ELECTRONIC TECHNOLOGY Co., LTD
 全球 互联零组件制造企业

TOLERANCE UNLESS OTHERWISE STATED:
 Up to 5 ±0.2
 Above 5 ~ 15 ±0.3
 Above 15 ~ 30 ±0.4
 Above 30 ~ 50 ±0.5
 Angle ±0.3°

DRAWN BY:	DATE	MAT'L	TITLE	JACK
Jack Lu	04/12/19	FINISH	MODLE	3.5mm PHONE JACK 防水型
CHECKED BY:	DATE	SCALE	DWG NO.	PJ-WP35408E-S404
Jacky Chen	04/12/19	1:1	PART NO.	PJ-WP35408E-S404
APPROVED BY:	DATE	SHEET NO.	1 of 1	
Tony Kao	04/12/19			

ITEM NO.	DESCRIPTION	DRAWN	DATE