



PCB LAYOUT MOUNTING PATTERN

SPECIFICATIONS

Electrical:

- 1.Voltage Rating : 125 VAC RMS
- 2.Current Rating : 1.5 AMP
- 3.Contact Resistance : 30 mΩ MAX
- 4.Insulation Resistance : 500 MΩ MIN. @500 VDC
- 5.Dielectric Strength : 1,000 VAC RMS 50 HZ 1 MIN

Mechanical:

- 1.Housing : PBT
- 2.Contact : Phosphor Bronze , Gold Plating over Nickel
- 3.Shield : Copper Alloy , Nickel Plated

Environmental:

- 1.Operation Temperature : -20°C ~ +70°C
- 2.Storage Temperature : -40°C ~ +85°C

KSD 科斯达电子科技有限公司
 SWITCH CONNECTOR KSD ELECTRONIC TECHNOLOGY Co., LTD
 全球 互联零组件制造企业

TOLERANCE UNLESS OTHERWISE STATED :
 Up to 5 ±0.2
 Above 5 ~ 15 ±0.3
 Above 15 ~ 30 ±0.4
 Above 30 ~ 50 ±0.5
 Angle ±0.3°

3RD. ANGEL'S

UNITS MM

DRAWN BY:	DATE	MAT'L	TITLE	RJ45
Jack Lu	01/16/20	FINISH	MODLE	RJ45 1X1 屏蔽背部双弹 带灯 左绿右橙绿
CHECKED BY:	DATE	SCALE	DWG NO.	RJ45-5JA81B-GOG-S307
Jacky Chen	01/16/20	1 : 1	PART NO.	RJ45-5JA81B-GOG-S307
APPROVED BY:	DATE	SHEET NO.		
Tony Kao	01/16/20	1 of 1		

I	更新LED端子編號	Jack	011620
ITEM NO.	DESCRIPTION	DRAWN	DATE