



SPECIFICATIONS

Model No.	X(mm)
SK-12D02S-GC2	2mm
SK-12D02S-GC3	3mm
SK-12D02S-GC4	4mm
SK-12D02S-GC5	5mm
SK-12D02S-GC6	6mm
SK-12D02S-GC7	7mm
SK-12D02S-GC8	8mm
SK-12D02S-GC9	9mm

Rating	DC 50V , 0.5A
Circuit	1P - 2T
Timing	Non - Shorting
Contact Resistance	50mΩ Max.
Insulation Resistance	100MΩ Min.
Operating Force	250gf ±100gf
Operating Life (cycle)	10,000 Min.

NO.	DESCRIPTION	QTY	MATERIAL	REMARK
6	SPRING PLATE	1	PHOSPHOR BRONZE	Natural
5	CONTACT CLIP	1	PHOSPHOR BRONZE	Ag-Plated
4	TERMINAL	3	BRASS	Ag-Plated
3	BASE	1	PHENOL IC RESIN	Natural
2	KNOB	1	PA9T	Black
1	FRAME	1	SPCC	Ni-Plated

KSD 科斯达电子科技有限公司
 SWITCH CONNECTOR KSD ELECTRONIC TECHNOLOGY Co., LTD
 全球 互联零组件制造企业

TOLERANCE UNLESS OTHERWISE STATED:
 Up to 5 ±0.2
 Above 5 ~ 15 ±0.3
 Above 15 ~ 30 ±0.4
 Above 30 ~ 50 ±0.5
 Angle ±0.3

3RD. ANGEL'S

UNITS MM

DRAWN BY:	DATE	MAT'L	TITLE	SWITCH
Jack Lu	01/14/22		MODLE	SLIDE SWITCH
CHECKED BY:	DATE	FINISH	DWG NO.	SK-12D02S-GCx-S191
Jacky Chen	01/14/22		PART NO.	SK-12D02S-GCx-S191
APPROVED BY:	DATE	SCALE	SHEET NO.	1 of 1
Tony Kao	01/14/22	1 : 1		

ITEM NO.	DESCRIPTION	DRAWN	DATE

SIZE A4
 VER R