

P.C.B LAYOUT MOUNTING PATTERN

PIN No.	Dimensions(mm)			PIN No.	Dimensions(mm)		
	A	B	C		A	B	C
02	3.80	1.90	0.80	13	12.60	10.70	9.60
03	4.60	2.70	1.60	14	13.40	11.50	10.40
04	5.40	3.50	2.40	15	14.20	12.30	11.20
05	6.20	4.30	3.20	16	15.00	13.10	12.00
06	7.00	5.10	4.00	17	15.80	13.90	12.80
07	7.80	5.90	4.80	18	16.60	14.70	13.60
08	8.60	6.70	5.60	19	17.40	15.50	14.40
09	9.40	7.50	6.40	20	18.20	16.30	15.20
10	10.20	8.30	7.20	21	19.00	17.10	16.00
11	11.00	9.10	8.00	22	19.80	17.90	16.80
12	11.80	9.90	8.80				

SPECIFICATIONS

- 1.Current rating : 0.3A AC , DC
- 2.Voltage rating : 30V AC , DC
- 3.Temperature rating : -25°C ~ +85°C


Material:

- 1.Housing : LCP
- 2.Contact : PhosphorBronze,Gold Plated over all Nickel
- 3.Peg : Brass, Gold Plated over all Nickel

KSD 科斯达电子科技有限公司
 SWITCH CONNECTOR KSD ELECTRONIC TECHNOLOGY Co., LTD
 全球 互聯零組件 制造企业

TOLERANCE UNLESS OTHERWISE STATED:
 Up to 5 ±0.2
 Above 5 ~ 15 ±0.3
 Above 15 ~ 30 ±0.4
 Above 30 ~ 50 ±0.5
 Angle ±0.3

3RD. ANGEL'S



UNITS MM

DRAWN BY: Jack Lu DATE: 11/30/22
 CHECKED BY: Jacky Chen DATE: 11/30/22
 APPROVED BY: Tony Kao DATE: 11/30/22

MAT'L		TITLE	CONNECTOR
FINISH		MODLE	WAFER 0.8mm . SMT 90度
SCALE	1 : 1	DWG NO.	WF-0801RSxx-S149
SHEET NO.	1 of 1	PART NO.	WF-0801RSxx-S149

SIZE A4
 VER R2

ITEM NO.	DESCRIPTION	DRAWN	DATE
2	更新Peg鍍層	Jack	113022
1	更新Contact鍍層	Jack	112422