











P.C.B LAYOUT
TOP VIEW

P.C.B LAYOUT
BOTTOM VIEW



(Ø3.50mm 4 POLE PLUG DETAIL DRAWING)



SPECIFICATION

- 1.Rating : 12V ; 1.0A ;
- 2.Contact resistance : $\leq 100m\Omega$;
- 3.Insulation resistance : $\geq 100M\Omega$;
- 4.Withstand voltage : 500VAC ;
- 5.Insertion and extraction force : 3-30N;
- 6.life test : 5,000 cycles °

7	SEPARATOR	1	PPA ;COLOR BLACK
6	HOUSING	1	PPA ;COLOR BLACK
5	CONTACT 5#	1	PHOSPHOR BRONZE; NICKEL UNDER PLATING OVERALL,GOLD PLATING ON SOLDER AREA ;GOLD PLATING ON CONTACT AREA
4	CONTACT 4#	1	SUS; NICKEL UNDER PLATING OVERALL,GOLD FLASH PLATING ON SOLDER AREA ;GOLD FLASH PLATING ON CONTACT AREA
3	CONTACT 3#	1	SUS; NICKEL UNDER PLATING OVERALL,GOLD FLASH PLATING ON SOLDER AREA ;GOLD FLASH PLATING ON CONTACT AREA
2	CONTACT 2#	2	SUS; NICKEL UNDER PLATING OVERALL,GOLD FLASH PLATING ON SOLDER AREA ;GOLD FLASH PLATING ON CONTACT AREA
1	CONTACT 1#	1	PHOSPHOR BRONZE; NICKEL UNDER PLATING OVERALL,GOLD PLATING ON SOLDER AREA ;GOLD PLATING ON CONTACT AREA
ITEM	PART NAME	Q'TY	MATERIAL

广东科斯达电子科技有限公司
GUANG DONG KE SI DA ELECTRONIC TECHNOLOGY CO., LTD.

TOLERANCE UNLESS OTHERWISE STATED :
Up to 5 ± 0.2
Above 5 ~ 15 ± 0.3
Above 15 ~ 30 ± 0.4
Above 30 ~ 50 ± 0.5
Angle $\pm 0.3^\circ$

3RD. ANGEL'S



UNITS

MM

DRAWN BY:	DATE	MAT'L	TITLE	JACK
Jack Lu	09/05/24	FINISH	MODLE	PHONE JACK
CHECKED BY:	DATE	SCALE	DWG NO.	PJ-S32308F-S457
Jacky Chen	09/05/24	1 : 1	PART NO.	PJ-S32308F-S457
APPROVED BY:	DATE	SHEET NO.	1 of 1	
Tony Kao	09/05/24			

ITEM NO.	DESCRIPTION	DRAWN	DATE